



SUPER SUCTION 0.5 HP MONOBLOC PUMP

- FITTED WITH THERMAL OVERLOAD PROTECTOR
- DESIGNED TO WORK EVEN AT LOW VOLTAGE
- POWDER COATED FOR LONG LIFE
- GUN METAL IMPELLER
- DOUBLE Z BEARINGS
- 60 FEET TOTAL HEAD
- DISCHARGE - 1800 LPH
- 30 FEET SUCTION
- 2880 rpm



SUPER SUCTION 1 HP MONOBLOC PUMP

- FITTED WITH THERMAL OVERLOAD PROTECTOR
- DESIGNED TO WORK EVEN AT LOW VOLTAGE
- POWDER COATED FOR LONG LIFE
- GUN METAL IMPELLER
- DOUBLE Z BEARINGS
- 80 FEET TOTAL HEAD
- DISCHARGE - 2400 LPH
- 30 FEET SUCTION
- 2880 rpm

TECHNICAL SPECIFICATIONS

MODEL	Color	Voltage	Watts	Sucton Head	Total Head	Discharge	Warranty	Weight (kg)
SUPER 0.5 H.P	ORANGE	230 v	0.37 Kw	25 ft	90 ft	2600 lph	1.5 yr	6.500 K.g (approx.)
SUPER 1 H.P	ORANGE	230 v	0.75 Kw	25 ft	120 ft	3000 lph	1.5 yr	9.300 K.g (approx.)
MAX 0.5 H.P	YELLOW	230 v	0.37 Kw	25 ft	100 ft	2900 lph	1.5 yr	7.300 K.g (approx.)
MAX 1 H.P	YELLOW	230 v	0.75 Kw	25 ft	130 ft	4300 lph	1.5 yr	9.900 K.g (approx.)
SHALLOW WELL 0.5 H.P	GREEN	230 v	0.37 Kw	30 ft	75 ft	3500 lph	1.5 yr	13.5 Kg
SHALLOW WELL 1.1 H.P	GREEN	230 v	0.75 Kw	35 ft	90 ft	4500 lph	1.5 yr	18.6 Kg
SUPER SUCTION 1 H.P.	GREEN	230 v	0.75 Kw	30 ft	80 ft	2400 lph	1.5 yr	13 Kg
SUPER SUCTION 0.5 H.P.	GREEN	230 v	0.37 Kw	30 ft	60 ft	1800 lph	1.5 yr	11.5 Kg

LAZER INDIA (P) LTD.

Admin. Office: 43, Rajasthani Udyog Nagar, (Ground Floor), New Delhi-110033
Tel: +91-11 43970000, Website: www.lazerindia.com

FOR TRADE ENQUIRIES
Tel: +91 11 43970000
E-mail: sales@lazerindia.com

FOR CUSTOMER CARE
1800 1030 177 (TOLL FREE)
E-mail: customercare@lazerindia.com

Note: Kindly note that photographs shown here are indicative. Due to continuous improvements, the actual product at the time of supply may differ from the details given herein. Vardhman Group/Quality Home Appliances reserves the right to make changes in Data/Details without any prior notice.



SWITCH ON HAPPINESS



**SUPER 0.5 HP
MONOBLOC PUMP**



- FITTED WITH THERMAL OVERLOAD PROTECTOR
- DESIGNED TO WORK EVEN AT LOW VOLTAGE
- FORGED BRASS IMPELLER
- MECHANICAL SEAL
- SKF ZZ BALL BEARING
- 2880 RPM
- 90 FEET TOTAL HEAD
- 25 FEET SUCTION
- DISCHARGE - 2100 LPH

**MAX 0.5 HP
MONOBLOC PUMP**



- FITTED WITH THERMAL OVERLOAD PROTECTOR
- DESIGNED TO WORK EVEN AT LOW VOLTAGE
- FORGED BRASS IMPELLER
- MECHANICAL SEAL
- SKF ZZ BALL BEARING
- 2880 RPM
- 100 FEET TOTAL HEAD
- 25 FEET SUCTION
- DISCHARGE - 2500 LPH

**SHALLOW WELL 0.5 HP
MONOBLOC PUMP**



- FITTED WITH THERMAL OVERLOAD PROTECTOR
- DESIGNED TO WORK EVEN AT LOW VOLTAGE
- POWDER COATED FOR LONG LIFE
- C. I. CASTING IMPELLER & BODY
- DOUBLE Z BEARINGS
- HEAVY DUTY MOTOR
- 75 FEET TOTAL HEAD
- DISCHARGE - 3200 LPH
- 30 FEET SUCTION
- 2880 rpm

**SUPER 1 HP
MONOBLOC PUMP**



- FITTED WITH THERMAL OVERLOAD PROTECTOR
- DESIGNED TO WORK EVEN AT LOW VOLTAGE
- FORGED BRASS IMPELLER
- MECHANICAL SEAL
- SKF ZZ BALL BEARINGS
- 2880 RPM
- 120 FEET TOTAL HEAD
- 25 FEET SUCTION
- DISCHARGE - 2500 LPH

**MAX 1 HP
MONOBLOC PUMP**



- FITTED WITH THERMAL OVERLOAD PROTECTOR
- DESIGNED TO WORK EVEN AT LOW VOLTAGE
- FORGED BRASS IMPELLER
- MECHANICAL SEAL
- SKF ZZ BALL BEARINGS
- 2880 RPM
- 130 FEET TOTAL HEAD
- 25 FEET SUCTION
- DISCHARGE - 4000 LPH

**SHALLOW WELL 1.1 HP
MONOBLOC PUMP**



- FITTED WITH THERMAL OVERLOAD PROTECTOR
- DESIGNED TO WORK EVEN AT LOW VOLTAGE
- POWDER COATED FOR LONG LIFE
- C. I. CASTING IMPELLER & BODY
- DOUBLE Z BEARINGS
- HEAVY DUTY MOTOR
- 90 FEET TOTAL HEAD
- DISCHARGE - 4500 LPH
- 35 FEET SUCTION
- 2880 rpm